



PROPERTIES OF GRAPHITE GRADE ELLOR+18

GENERAL

Isomolded, very fine grain, high strength. high density, isotropic graphite. Maximum inert service temperature 5,000 F (2760 °C).
Standard Sizes: 308 x 620 x 1830 mm
308 X 620 x 915 mm

TYPICAL

APPLICATIONS

Formulated for EDM applications requiring medium surface finish and high metal removal rates.
Surface finish 4.5 to 9 Raµm.

PROPERTIES

	Typical Values	
	English Units	SI Units
Bulk Density	111 lbs/ft ³	1,78 g/cm ³
Grain Size	0.0005 inch	12 µm
Specific Resistance	0.00054 ohm-in	1370 µohm.cm
Flexural Strength	6,500 psi	45 MPa
Tensile Strength	4,200 psi	29 MPa
Compressive Strength	14,300 psi	99 MPa
Hardness (Shore)	55	55
Hardness (Rockwell L)	98	98
Coefficient of Thermal Expansion (400 to 500°C)	2.9 x 10E-6/°F	5,2 x 10E-6/°C
Porosity	12%	12%
Thermal Conductivity	55 Btu-Ft/Ft ² Hr°F	95 W/m°C
Ash	400 ppm	400 ppm

13-May-2010 Rev 01

The specification or data herein contained are only given for indication, without any undertakings whatsoever. Their publication does not suggest the matter is free of any rights whatsoever. Furthermore, due to constant evolution of techniques and norms, we reserve the right to modify, at any time, the characteristics and specifications contained in this document. MERSEN refuses all and any responsibility concerning their use whatever the purpose or application. Any copy, reproduction or information herein contained, in whole or in part, made without MERSEN written consent, is forbidden according to the laws of France and particularly the law nr. 92-597 of July 1st 1992 relating to the copyright.

In North America contact:

Mersen USA St Marys-PA Corp.

215 Stackpole Street
Saint Marys, PA 15857 USA
Tel: (814) 781 - 1234
Fax: (814) 781 - 8570

In Europe contact:

Mersen France Gennevilliers S.A.S

BP 148 - 41, rue Jean - Jaurès
F - 92231 Gennevilliers - France
Tel: (33) 1 41 85 43 00
Fax: (33) 1 41 85 43 15